

# 9-30422 Air heater for freezer applications

### Description

The Air Heater Box is designed to raise the temperature of the air drawn from a very cold environment by passing it across a heating element before it passes into the detector. In this manner, the problem of condensation on sampling pipeworkexternal to the protected area is minimised. Warming the air sample will also ensure the components of the detector operate within the specified temperature tolerances, and it reduces the possibility of surface condensation.

#### **Overview**

The AirSense Stratos range of High Sensitivity Aspirating Smoke Detectors are suitable for installation within an area only if the ambient temperature is expected to be above 0°C (the minimum operating temperature of a detector is typically -10°C: check the specification of the particular detector in question). Where the air temperature in the protected area is consistently below this temperature, it is imperative that the detector is mounted outside the protected area, in an environment where the temperature meets that specified for the detector. However, the sampled air from the protected area must be conditioned before it is passed into the detector.



#### **Details**

- Suitable for cold stores / cold rooms
- Mutiple sampling inlets

## 9-30422 Air heater for freezer applications

### **Technical specifications**

Electrical	
Operating voltage	220 VAC
Current consumption	1.1 A (max)
Sampling pipe	
Inlet quantity	4
Inlet size	27 mm OD
Exhaust	2
Exhaust size	27 mm ID
Physical	
Physical dimensions	172 x 300 x 212 mm (W x H x D)
Net weight	2.8 kg
Cable entries	1 x M20
Environmental	
Operating temperature	-10 to +60°C
Relative humidity	0 to 90% noncondensing
Environment	Indoor
Regulatory	
Certification	EN54-20



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.