

# **DP2061N**

### Aritech 2000 Series addressable optical smoke detector

#### General

The DP2061N is a 2000 series protocol, addressable optical detector. It is equipped with a field-exchangeable optical block and is fully CPD certified. This optical detector combines a low profile design with dual alarm LEDs for 360° alarm visibility, and features a remote indicator output as standard.

### **User friendly**

Every detector is equipped with an internal self-test feature. This test may be activated from the fire panel and allows the detector to perform a self-test for which the result is reported to the panel.

All detectors are individually identified by setting an address through 2 rotary switches. The address is straight numerical and does not require binary or hexadecimal conversions and therefore significantly reduces the risk of incorrect addressing.

#### Maintenance friendly

The DP2061N features a disposable optical chamber. This allows the detector to be easily serviced without the need for specialised equipment in the field and without operating through an exchange pool of any kind. A self-test feature as well as drift compensation and contamination warning is provided when used with compatible Aritech fire panels.

All 2000 series detectors are compatible with a standard base, which makes them easily interchangeable.

#### State of the art communication

An enhanced protocol ensures the overall integrity and error-free operation of the system, without compromising speed. The 2000 series protocol provides features such as CRC error checking and multiple bus cycle codes to enable advanced features of the panel to detector communication.

#### **Extended applications**

A comprehensive 2000 series range of detectors and accessories complement the DP2061N detector. Appart from a complete detector line as well as a full line of manual call points, accessories such as isolators, sounder circuit controllers, zone monitor units and a variety of I/O modules are also available.



#### Details

- Optical smoke detector with configurable sensitivity levels
- Full diagnostic self testing
- · Remote signaling capabilities
- Enhanced digital communication protocol
- Easy numeric addressing (1-128) for fast and fault free installation
- Field exchangeable optical chamber for easy on-site maintenance

# **DP2061N**

# Aritech 2000 Series addressable optical smoke detector

## **Technical specifications**

General		
Status indication	Dual red alarm LED	
Compatibility	Aritech 2000 systems	
Alarm levels	5	
Connectivity	2000 Series detector bases	
Addressing method	Rotary switch	
Electrical		
Power supply type	Loop powered	
Operating voltage	17 to 28 VDC	
Current consumption	350 μA (quiescent at 24 VDC) 4 mA (alarm at 24 VDC)	
Detection		
Detection principle	Optical light scatter	
Monitoring	Alarm threshold, Contamination level	
Sensitivity	Configurable	
Coverage area	<80 m²	
Output		
Output quantity	1	
Output type and rating	Remote indicator	
Programmable	No	
Remote alarm output	4 mA	
Physical		
Physical dimensions	100 x 50 mm (Ø x H)	
Net weight	115 g	
Colour	Cloud white (RAL 9001)	
Mounting type	Base mount	
Material (body)	Plastic	
Environmental		
Vandal proof	No	
Operating temperature	-10 to +60°C	
Storage temperature	-10 to +70°C	
Application temperature (typical)	+25°C	
Relative humidity	10 to 95% noncondensing	
Environment	Indoor	
IP rating	IP43	
Regulatory		
Compliancy	CE, REACH, RoHS 2, WEEE	
Certification	CPR	
<u> </u>		

#### **Compatible products**

Category	Reference	Description
Detection	DB2002	2000 Series standard point detector
device		base
Detection	DB2002U	2000 Series wide point detector base
device		
Detection	DB2004	2000 Series deep point detector base
device		
Detection	DB2016	2000 Series base with isolator
device		
Detection	DP2CAP-ICT	[10 pack] Aritech Dx700 / Dx2000
device		Series insect protection caps
Notification	AI672	Dx700 / Dx2000 series conventional
device		remote indicator
Notification	AI673	Dx700 / Dx2000 series conventional
device		remote indicator with buzzer
Notification	DB2368IAS-W	2000 Series sounder base with isolator,
device		white



EN54-7

Standards

As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.