

FC-315-CA2

Fusion Wireless Ceiling Mount Sounder/VAD (Red)

General

The FC-315-CA2 is a RED, fire alarm sounder/VAD combination to be used with a wireless base. The VAD lens is specifically designed to have maximum coverage in ceiling mount applications. The 32 tone device is suitable for indoor use.

The sounder is quick and easy to install into the wireless base with a simple turn and lock mechanism.

The Range

The Fusion series consists of:

- Optical Smoke Detectors
- Multisensor Smoke Detectors
- A1R Heat Detectors
- CS Heat Detectors
- Sounders in red and white
- Combination Sounder VIDs and VADs
- Manual Call Points
- Interface Modules

Operating Principle

Wireless devices are often installed in buildings where wiring presents a challenge because the fabric of the building or its design is negatively affected by the use of cables. It could also be difficult to introduce cable runs into heritage buildings. It is for these architecturally sensitive buildings that the Fusion series was developed.

Every Fusion device is assigned an address from its base. This address is converted by the Fusion wireless loop interface to a device address similar to a wired device connected directly to the loop wiring.



Details

- Dual band 868 MHz operation
- 32 selectable tones
- 0.5 Hz or 1 Hz VAD flash selection
- Integrated audio monitoring
- Volume control possible
- Anti tamper locking mechanism
- Third party EN certified
- Easy to install
- Proven technology

FC-315-CA2

Fusion Wireless Ceiling Mount Sounder/VAD (Red)

Technical specifications

General

Compatibility	Wireless base FC-171-002
---------------	--------------------------

Electrical

Power supply type	Batteries
Operating voltage	2.8 to 5 VDC

Sounder

Output level	< 99 dB(A) @ 1 m (Tone dependant)
Output level adjustment	Analogue
Frequency	Selectable
Selectable tones	32
No. of stages	2

VAD

Colour	White
Rating	C-3-15
Floor coverage	< 112 m ²
Flash frequency	0.5 or 1 Hz

Physical

Physical dimensions	120 x 145 mm (Ø x H) - Including base
Net weight	650 g - Including base
Colour	Red
Mounting type	Base mount
Mounting position	Ceiling
Mounting height	< 3 m
Mounting base	Wireless

Environmental

Vandal proof	No
Operating temperature	-10°C to 55°C
Storage temperature	5°C to 30°C
Relative humidity	< 95% non-condensing
Environment	Indoor
IP rating	IP54

Regulatory

Compliance	CE, REACH, RoHS 2, WEEE
Certification	CPR
Standards	EN54-3, EN54-23



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 14 June 2024 - 15:35